

Rottweg 17 • D 48683 Ahaus Tel. (0 25 61) 93 84-0 Fax (0 25 61) 93 84 36 Internet: www.ab-maschinen.de E-Mail: info@ab-maschinen.de Schweißtechnik
Lagereinrichtungen
Industriebedarf
Werksvertretungen
Gebrauchtmaschinen

KNUTH KB 1400 (1008-9131205)



Control type konventionell

Construction year 2009

Machine no. 1008-9131205

Make KNUTH

LocationAhaus

- ** current new price approx. 60.000 euros
- ** Special price on request

The heavy universal bed milling machine offers wide guides and high
Drive power for superior cutting performance and is with your
Extensive equipment ideal for plant and mechanical engineering
suitable. The heavy vertical milling head can be swiveled right and left,
The quill can be moved manually and the spindle speed can be adjusted
continuously regulate. The feed in the Y and X axes can be done via a robust
Manual transmission can be varied. All axes have rapid traverse and the
Large clamping table offers plenty of space for workpieces and clamping devices.

It is not the machine table (with the workpiece) that is moved in the Z axis, but rather the milling head - greater stability and lower vibrations lead to more Precision with very high table load capacity! This is further reinforced Effect through the large, heavy gray cast iron frame (Meehanite) and the extremely wide flat guides.

Furnishing:

- Continuous speed regulation by frequency converter
- Rigid right-angle guides guarantee lasting accuracy
- Meehanite gray cast iron frame
- \pm 30° swiveling milling head
- Hardened and ground guideways in all axes
- The machine is equipped with a 3-axis position display as standard
- * Greater work accuracy
- * Lower error rate
- * Greater manufacturing reliability
- * Significant time savings
- * Increased productivity
- * Easy to read display
- * User friendly features
- * Clearly arranged keyboard
- * Resolution 0.01/0.005mm
- Central lubrication
- Coolant device
- Operation manual
- * Machine link:

http://mhp.logotech.de/hpm/v7/Datenblatt/datenblatt.php?machineno=1008-9131205

Machine attributes

 x-travel:
 950 mm

 y-travel:
 400 mm

 z-travel:
 500 mm

 tool taper:
 ISO 50

 throat:
 510 mm

 quill stroke:
 105 mm

spindle turning speed range: 18 - 1800 U/min feeds: 16 - 627 mm/min rapid traverse: 1670 mm/min table-size: 1400 x 400 mm

table load capacity: 500 kg

T-slots: 3x14x100 mm distance spindle /table: 150 - 650 mm engine output: 9,0 kW weight: 3660 kg

dimensions of the machine ca.: 2290 x 1770 x 2120 mm

Machine images







Rottweg 17 • D 48683 Ahaus Tel. (0 25 61) 93 84-0 Fax (0 25 61) 93 84 36 Internet: www.ab-maschinen.de E-Mail: info@ab-maschinen.de Schweißtechnik
Lagereinrichtungen
Industriebedarf
Werksvertretungen
Gebrauchtmaschinen













Rottweg 17 • D 48683 Ahaus Tel. (0 25 61) 93 84-0 Fax (0 25 61) 93 84 36 Internet: www.ab-maschinen.de E-Mail: info@ab-maschinen.de Schweißtechnik
Lagereinrichtungen
Industriebedarf
Werksvertretungen
Gebrauchtmaschinen

