



Rottweg 17 • D 48683 Ahaus
Tel. (0 25 61) 93 84-0
Fax (0 25 61) 93 84 36
Internet: www.ab-maschinen.de
E-Mail: info@ab-maschinen.de

Schweißtechnik
Lagereinrichtungen
Industriebedarf
Werksvertretungen
Gebrauchtmaschinen

MVD HGM 3010 HH (1008-9325144)

© A + B Werkzeuge Maschinen Handels GmbH



Control type
NC

Construction year
2006

Machine no.
1008-9325144

Make
MVD

Location
Ahaus

** from a maintenance workshop

** New price ~ 40.000 euros

Furnishing:

- hydraulic swing cut shears
- NC positioning control / digital display of the backgauge
- * robust backgauge with high quality ball screws
- Machine frame & cutter bar made of sturdy welded construction
- the proven swing cut construction enables a small knife angle
- * for optimal cutting quality and low distortion on the workpiece
- hydraulically operated hold-down devices
- Ball rollers in the support table
- 1x side stop
- 2x support arms
- foot switch

** Special accessories included:

- pneumatic sheet holding device

Machine attributes

sheet width:	3100 mm
plate thickness:	10,0 mm
thickness at "Niro-steel":	6,0 mm
cutting angle:	2,0 °
no. of strokes:	13/18 Hub/min
back stop - adjustable:	max. 1.000 mm
down holder:	14 Stück
work height max.:	880 mm
Control:	PRG 911
oil volume:	265 l
voltage:	400 V
engine output:	22,0 kW
weight:	9600 kg
range L-W-H:	4275 x 2100 x 2065 mm

Machine images





Rottweg 17 • D 48683 Ahaus
Tel. (0 25 61) 93 84-0
Fax (0 25 61) 93 84 36
Internet: www.ab-maschinen.de
E-Mail: info@ab-maschinen.de

Schweißtechnik
Lagereinrichtungen
Industriebedarf
Werkvertretungen
Gebrauchtmaschinen

© A + B Werkzeuge Maschinen Handels GmbH



© A + B Werkzeuge Maschinen Handels GmbH



© A + B Werkzeuge Maschinen Handels GmbH



© A + B Werkzeuge Maschinen Handels GmbH

MVD INAN		takim tezgahları sanayi a.ş. machine tool industry co.		CE
Fab: 1. Organize Sanayi Bölgesi Budaközü Sk. No: 16 Tel: (+ 90.332) 248 25 40 (Pbx) Fax: 248 53 80 KONYA / TURKEY				
HYDRAULIC SWING-BEAM SHEAR				
Type HGM	3010	Series No	080528	
Year of Manufacture	2005	Main Motor Power	72 kW.	
Max. Cutting Length	3000 mm.	Voltage	400 Volt	
Max. Cutting Thickness	10 mm.	No. of phase	3+6ND	
Max. Hydraulic Pressure	300 Bar	Frequency	50 Hz.	
Approximate Weight	10000 kg.	Overall full load current	45 A.	
In. Light beam distance from blades	1800 mm			