



Rottweg 17 • D 48683 Ahaus
Tel. (0 25 61) 93 84-0
Fax (0 25 61) 93 84 36
Internet: www.ab-maschinen.de
E-Mail: info@ab-maschinen.de

Schweißtechnik
Lagereinrichtungen
Industriebedarf
Werksvertretungen
Gebrauchtmaschinen

OMAG CE 254 S (1008-9325145)



Control type
konventionell

Machine no.
1008-9325145

Make
OMAG

Location
Ahaus

Furnishing:

- electrical backgauge, with SONY digital display
- welded monoblock steel construction
- Special steel knives that can be used on both sides, hardened
- Front control panel with emergency stop button
- manual cutting gap adjustment
- Side stop and support arm
- Foot switch with foot release

Machine attributes

sheet width:	2550 mm
plate thickness:	4,0 mm
thickness at "Niro-steel":	3,0 mm
no. of strokes:	39/25 Hub/min
cutting angle:	1°5
table height:	810 mm
distance between columns:	2700 mm
back stop - adjustable:	600 mm
engine output:	5,75 kW
weight of the machine ca.:	3590 kg.
range L-W-H:	3150 x 2150 x 1310 mm

Machine images





Rottweg 17 • D 48683 Ahaus
Tel. (0 25 61) 93 84-0
Fax (0 25 61) 93 84 36
Internet: www.ab-maschinen.de
E-Mail: info@ab-maschinen.de

Schweißtechnik
Lagereinrichtungen
Industriebedarf
Werksvertretungen
Gebrauchtmaschinen



© A + B Werkzeuge Maschinen Handels GmbH

omag
abbiategrasso milano ITALY tel. 02-9465781
hydraulische tafelschere

masch Nr.
modell
schnittleistung

schnittleistung

blechsstärke

bestimmt die maximale Schnittleistung

blechsstärke	St 37	St 50	St 60	St 70	St 80	St 90	St 100
1	4.5	3.5	2.5	1.5	1.0	0.5	0.2
2	3.0	2.0	1.5	1.0	0.5	0.2	0.1
3	2.0	1.5	1.0	0.5	0.2	0.1	0.05
4	1.5	1.0	0.5	0.2	0.1	0.05	0.02
5	1.0	0.5	0.2	0.1	0.05	0.02	0.01
6	0.5	0.2	0.1	0.05	0.02	0.01	0.005

mod. 101

officine